


# Hot Runner Quote Request Form 1 of 2

**QUOTE FAX HOTLINES AVAILABLE or visit [www.dme.net](http://www.dme.net)**

**United States: 888-808-4363 • Canada: 800-461-9965 • International: 248-398-7394**

Stat No.	<b>Form AE001 Rev 5.16.11</b>		Date
<b>Tech Service Approval Required for Firm Quote</b>			Phone
<b>QUOTE TYPE:</b> <input type="checkbox"/> Preliminary <input type="checkbox"/> Firm			Fax
<b>Customer's In-House Date Requirement</b>			E-mail
			Sales Rep
Company			Contact
Address			Phone
Address			Fax
City			E-mail
State	ZIP	Acct#	End User
Molding Material			Contact
Manufacturer			Phone
Filler	<input type="checkbox"/> None <input type="checkbox"/> Glass <input type="checkbox"/> Other Percent %		
Flame Retardant	<input type="checkbox"/> Yes <input type="checkbox"/> No Mold Flow Index		
Color Changes	<input type="checkbox"/> Yes <input type="checkbox"/> No		Mold Temp deg.
New Mold	<input type="checkbox"/> Retrofit	DME Mold Base to be Quoted	
Mold Base Size	Mold Base Drawings Supplied		
Gating Into	<input type="checkbox"/> Part <input type="checkbox"/> Dimple <input type="checkbox"/> Runner		
Gate Style	<input type="checkbox"/> Sprue <input type="checkbox"/> Ext Sprue <input type="checkbox"/> Bodiless Point <input type="checkbox"/> Full Body Point Ring Gate <input type="checkbox"/> Wear Resistant Needle <input type="checkbox"/> Other		
Number of Drops	Number of Cavities		
Part Name	Part Number	Job#	
Part Drawing Supplied	<input type="checkbox"/> Yes <input type="checkbox"/> No		Sample Supplied <input type="checkbox"/> Yes <input type="checkbox"/> No
Wall Thickness of Part			CAD Data Supplied <input type="checkbox"/> Yes <input type="checkbox"/> No
Part Weight	<input type="checkbox"/> Grams <input type="checkbox"/> Ounces		Total Shot Weight
Plate Material	<input type="checkbox"/> #2 <input type="checkbox"/> #7 (Stainless Steel) <input type="checkbox"/> Other <i>Manifold Plate is H-13 Resulfurized or equivalent unless otherwise specified</i>		
	Preferred Layout (H), (X), (INLINE) etc.		
	Flow Diameters	Balanced <input type="checkbox"/> Yes <input type="checkbox"/> No	
<b>Options Required</b>			
<input type="checkbox"/> Leader Pins in Nozzle Plate	<input type="checkbox"/> Special Connectors	<input type="checkbox"/> Water Cooled Gate Inserts	
<input type="checkbox"/> Mounting Bolts from Parting Line	Describe:	<input type="checkbox"/> Manifold Extension Nozzle	
<input type="checkbox"/> Mounting Bolts from Back Side	<input type="checkbox"/> Recessed Connectors	<input type="checkbox"/> Mold Flow Analysis	
<input type="checkbox"/> Special Terminal Box	<input type="checkbox"/> Flush Mounted Connectors	<input type="checkbox"/> Heater Pullers	
Describe:	<input type="checkbox"/> Cavity Mounting Screws		
<b>Notes</b>			

# Hot Runner Quote Request Form 2 of 2

Fax completed form to 248-544-5707 or email [appl\\_eng@dme.net](mailto:appl_eng@dme.net)

Stat No.		Form AE001 Rev 7.7.11
Company		Date
SYSTEM TYPE (REQUIRED)		QUOTE STYLE (REQUIRED)
<b>HOT ONE (Tubular or Cartridge)</b>		
Nozzle Series (Standard)	<input type="checkbox"/> 250 <input type="checkbox"/> 375 <input type="checkbox"/> 625	<input type="checkbox"/> Tubular Package System
Nozzle Series (High Performance)	<input type="checkbox"/> 250 <input type="checkbox"/> 375	<input type="checkbox"/> Tubular Manifold & Comp
Nozzle Series (Gate Mate)	<input type="checkbox"/> Standard <input type="checkbox"/> Jumbo <input type="checkbox"/> Mini Square Coil <input type="checkbox"/> Mini Cast In <input type="checkbox"/> Front Load <input type="checkbox"/> Non-Front Load <input type="checkbox"/> Gate Shell Insulators	<input type="checkbox"/> Tubular Manifold Only
<b>COOL ONE</b>		
Probe Type	<input type="checkbox"/> AFPN <input type="checkbox"/> AFP <input type="checkbox"/> AFIP	<input type="checkbox"/> Package System
Gate Inserts	<input type="checkbox"/> Yes <input type="checkbox"/> No	
Quantity of Tubes	Primary Bore Size <input type="checkbox"/> 1.250 <input type="checkbox"/> 2.000	
	Secondary Bore Size <input type="checkbox"/> 1.250 <input type="checkbox"/> 2.000	
	Primary Bore Size <input type="checkbox"/> 1.250 <input type="checkbox"/> 2.000	
<b>VALVE GATE</b>		
<input type="checkbox"/> Single	In-Line <input type="checkbox"/> 200 <input type="checkbox"/> 400	<input type="checkbox"/> Air or <input type="checkbox"/> Hydraulic
<input type="checkbox"/> Offset	Secondary Bore Size <input type="checkbox"/> Bodiless <input type="checkbox"/> Full Body	
Multi-Valve Gate	Nozzle Series <input type="checkbox"/> 50 <input type="checkbox"/> 200 <input type="checkbox"/> 500 <input type="checkbox"/> 800 <input type="checkbox"/> 1000	<input type="checkbox"/> Package System
	Tip Series <input type="checkbox"/> Bodiless <input type="checkbox"/> Full Body <input type="checkbox"/> Sprue <input type="checkbox"/> Air <input type="checkbox"/> Hydraulic	<input type="checkbox"/> Unitized – If "Unitized" System, Plate (s) to be manufactured by: <input type="checkbox"/> DME <input type="checkbox"/> Customer
<b>GALAXY</b>		
(Z-Dim) Max 135mm [5.314 in.] / Min 27mm [1.063 in.]		<input type="checkbox"/> Package System Only
<input type="checkbox"/> Gate Shell Insulators		<input type="checkbox"/> Unitized – Select: <input type="checkbox"/> 2-Drop <input type="checkbox"/> 4-Drop
Nozzles <input type="checkbox"/> 25mm <input type="checkbox"/> 8mm		
<b>STELLAR</b>		
Round MNA Quantity Required:		<b>Package System</b>
Gate Circle Pitch (dia.)	<input type="checkbox"/> 40mm <input type="checkbox"/> 50mm <input type="checkbox"/> 70mm <input type="checkbox"/> 90mm	<input type="checkbox"/> MNA (Threaded)
Round MNA Quantity Required :		<input type="checkbox"/> Compression
Gate Pitch (2-Drop)	<input type="checkbox"/> 30mm <input type="checkbox"/> 40mm <input type="checkbox"/> 50mm <input type="checkbox"/> 70mm <input type="checkbox"/> 90mm	<input type="checkbox"/> Compression 6000 ('Z-Dim') Max 95mm [3.740in.]
Gate Pitch (4-Drop)	<input type="checkbox"/> 30mm In-line <input type="checkbox"/> 30mm x 30mm <input type="checkbox"/> 17mm x 21mm	<input type="checkbox"/> Unitized
Gate Pitch (6-Drop)	<input type="checkbox"/> 30mm (2 rows of 3)	
Gate Pitch (8-Drop)	<input type="checkbox"/> 30mm (2 rows of 4)	
Gate Pitch (12-Drop)	<input type="checkbox"/> 30mm (3 rows of 4)	
Gate Pitch (16-Drop)	<input type="checkbox"/> 30mm (4 rows of 4)	
<b>MNA (Threaded)</b>	(Z-Dim) Max 115mm [4.527 in.] / Min 13mm [0.52 in.]	<input type="checkbox"/> Manifold and Components – MNA (Threaded)
<b>Compression</b>	(Z-Dim) Max 125mm [4.921 in.] / Min 13mm [0.52 in.]	
Selected components verified to fit application by: <input type="checkbox"/> Sales <input type="checkbox"/> Tech Rep <input type="checkbox"/> Hot Runner Specialist <input type="checkbox"/> Applications Engineer		
Completed By:		Date
Tech Service Approval		Date
Applications Engineering Review		Date

Hot One Hot Runner Technology | Hot Runner Quote Request Form