

Lifting Holes



FOR QUOTING OR ORDERING, SPECIFY:

Lifting Holes

Lifting holes can be selected up to three per plate edge. They are available in top clamp plate, A-plate, B-plate, support plate, and bottom clamp plate.

Note that for safety reasons, only the recommended hole diameters (or larger) shown in the table are offered.

Diameter _____

Quantity in each plate _____

Plates with lift holes _____

(Prints required if not on center)

Lifting Holes can be used to install hoist rings for ease of handling. Mold base can be configured only with Lifting Holes which are appropriate for the specific mold base size. Refer to the D-M-E Mold Components catalog for a comprehensive selection of hoist rings.

Lifting Hole Diameters

BASE SIZE	PLATE THICKNESS	
	0.875	1.375
88-1118	1/2-13 UNC	1/2-13 UNC
1123-1524	5/8-11 UNC	5/8-11 UNC
1529-1829	5/8-11 UNC	3/4-10 UNC
1835-2429	5/8-11 UNC	1"-8 UNC
2435	N/A	1"-8 UNC

Lifting Holes

THREAD SIZE	S	T MAX.
1/2-13	1.00	1.38
5/8-11	1.25	1.75
3/4-10	1.50	2.00
1"-8	2.00	2.62

