

15 7/8" T-Series Mold Bases

NO. 1 OR NO. 2 STEEL ASSEMBLIES

All plates above ejector housing are No. 1 or No. 2 Steel, respectively.

NO. 3 STEEL ASSEMBLIES

"X-1", "X-2", and "B" Plates are No. 3 Steel. "A" -Clamping and Support Plates are No. 2 Steel.

NO. 7 STEEL ASSEMBLIES

Any or all plates available as requested.

X-1 = 0.875				15.875 x 16"		X-1 = 1.375				15.875 x 23.5		X-1 = 1.375				15.875 x 29.5	
X-2	B	C	H	ITEM NUMBER	NET WT.	X-2	B	C	H	ITEM NUMBER	NET WT.	X-2	B	C	H	ITEM NUMBER	NET WT.
1.875	1.375	3	12.25	1616T-17-13	808	1.875	1.375	3	12.75	1623T-17-13	1239	1.875	1.375	3	12.75	1629T-17-13	1555
	1.875	3.5	13.25	1616T-17-17	852		1.875	3.5	13.75	1623T-17-17	1304		1.875	3.5	13.75	1629T-17-17	1637
	2.375	3.5	13.75	1616T-17-23	888		2.375	3.5	14.25	1623T-17-23	1357		2.375	3.5	14.25	1629T-17-23	1703
2.375	1.375	3.5	13.25	1616T-23-13	852	2.375	1.375	3.5	13.75	1623T-23-13	1304	2.375	1.375	3.5	13.75	1629T-23-13	1637
	1.875	3.5	13.75	1616T-23-17	888		1.875	3.5	14.25	1623T-23-17	1357		1.875	3.5	14.25	1629T-23-17	1703
	2.375	3.5	14.25	1616T-23-23	924		2.375	3.5	14.75	1623T-23-23	1410		2.375	3.5	14.75	1629T-23-23	1770
2.875	1.375	3.5	13.75	1616T-27-13	888	2.875	1.375	3.5	14.25	1623T-27-13	1357	2.875	1.375	3.5	14.25	1629T-27-13	1703
	1.875	3.5	14.25	1616T-27-17	924		1.875	3.5	14.75	1623T-27-17	1410		1.875	3.5	14.75	1629T-27-17	1770
	2.375	3.5	14.75	1616T-27-23	960		2.375	3.5	15.25	1623T-27-23	1463		2.375	3.5	15.25	1629T-27-23	1836
3.375	1.875	4	15.25	1616T-33-17	969	3.375	1.875	4	15.75	1623T-33-17	1475	3.375	1.875	4	15.75	1629T-33-17	1852
	2.375	4	15.75	1616T-33-23	1005		2.375	4	16.25	1623T-33-23	1528		2.375	4	16.25	1629T-33-23	1918
	2.875	4.5	16.75	1616T-33-27	1049		2.875	4.5	17.25	1623T-33-27	1593		2.875	4.5	17.25	1629T-33-27	2000
3.875	1.875	4	15.75	1616T-37-17	1005	3.875	1.875	4	16.25	1623T-37-17	1528	3.875	1.875	4	16.25	1629T-37-17	1918
	2.375	4.5	16.75	1616T-37-23	1049		2.375	4.5	17.25	1623T-37-23	1593		2.375	4.5	17.25	1629T-37-23	2000
	2.875	4.5	17.25	1616T-37-27	1085		2.875	4.5	17.75	1623T-37-27	1646		2.875	4.5	17.75	1629T-37-27	2066
4.875	2.375	4.5	17.75	1616T-47-23	1121	4.875	2.375	4.5	18.25	1623T-47-23	1699	4.875	2.375	4.5	18.25	1629T-47-23	2133
	2.875	4.5	18.25	1616T-47-27	1157		2.875	4.5	18.75	1623T-47-27	1752		2.875	4.5	18.75	1629T-47-27	2199
	3.375	4.5	18.75	1616T-47-33	1193		3.375	4.5	19.25	1623T-47-33	1805		3.375	4.5	19.25	1629T-47-33	2266
5.875	2.875	4.5	19.25	1616T-57-27	1229	5.875	2.875	4.5	19.75	1623T-57-27	1858	5.875	2.875	4.5	19.75	1629T-57-27	2332
	3.875	4.5	20.25	1616T-57-37	1301		3.875	4.5	20.75	1623T-57-37	1963		3.875	4.5	20.75	1629T-57-37	2465
	4.875	4.5	21.25	1616T-57-47	1373		4.875	4.5	21.75	1623T-57-47	2069		4.875	4.5	21.75	1629T-57-47	2597
X-1 = 0.875				15.875 x 20"		X-1 = 1.375				15.875 x 26"		X-1 = 1.375				15.875 x 35.5	
X-2	B	C	H	ITEM NUMBER	NET WT.	X-2	B	C	H	ITEM NUMBER	NET WT.	X-2	B	C	H	ITEM NUMBER	NET WT.
1.875	1.375	3	12.25	1620T-17-13	1009	1.875	1.375	3	12.75	1626T-17-13	1371	1.875	1.375	3	12.75	1635T-17-13	1871
	1.875	3.5	13.25	1620T-17-17	1065		1.875	3.5	13.75	1626T-17-17	1443		1.875	3.5	13.75	1635T-17-17	1970
	2.375	3.5	13.75	1620T-17-23	1110		2.375	3.5	14.25	1626T-17-23	1501		2.375	3.5	14.25	1635T-17-23	2050
2.375	1.375	3.5	13.25	1620T-23-13	1065	2.375	1.375	3.5	13.75	1626T-23-13	1443	2.375	1.375	3.5	13.75	1635T-23-13	1970
	1.875	3.5	13.75	1620T-23-17	1110		1.875	3.5	14.25	1626T-23-17	1501		1.875	3.5	14.25	1635T-23-17	2050
	2.375	3.5	14.25	1620T-23-23	1155		2.375	3.5	14.75	1626T-23-23	1560		2.375	3.5	14.75	1635T-23-23	2130
2.875	1.375	3.5	13.75	1620T-27-13	1110	2.875	1.375	3.5	14.25	1626T-27-13	1501	2.875	1.375	3.5	14.25	1635T-27-13	2050
	1.875	3.5	14.25	1620T-27-17	1155		1.875	3.5	14.75	1626T-27-17	1560		1.875	3.5	14.75	1635T-27-17	2130
	2.375	3.5	14.75	1620T-27-23	1200		2.375	3.5	15.25	1626T-27-23	1618		2.375	3.5	15.25	1635T-27-23	2209
3.375	1.875	4	15.25	1620T-33-17	1211	3.375	1.875	4	15.75	1626T-33-17	1632	3.375	1.875	4	15.75	1635T-33-17	2228
	2.375	4	15.75	1620T-33-23	1256		2.375	4	16.25	1626T-33-23	1691		2.375	4	16.25	1635T-33-23	2308
	2.875	4.5	16.75	1620T-33-27	1311		2.875	4.5	17.25	1626T-33-27	1763		2.875	4.5	17.25	1635T-33-27	2407
3.875	1.875	4	15.75	1620T-37-17	1256	3.875	1.875	4	16.25	1626T-37-17	1691	3.875	1.875	4	16.25	1635T-37-17	2308
	2.375	4.5	16.75	1620T-37-23	1311		2.375	4.5	17.25	1626T-37-23	1763		2.375	4.5	17.25	1635T-37-23	2407
	2.875	4.5	17.25	1620T-37-27	1356		2.875	4.5	17.75	1626T-37-27	1821		2.875	4.5	17.75	1635T-37-27	2487
4.875	2.375	4.5	17.75	1620T-47-23	1401	4.875	2.375	4.5	18.25	1626T-47-23	1880	4.875	2.375	4.5	18.25	1635T-47-23	2566
	2.875	4.5	18.25	1620T-47-27	1446		2.875	4.5	18.75	1626T-47-27	1938		2.875	4.5	18.75	1635T-47-27	2646
	3.375	4.5	18.75	1620T-47-33	1491		3.375	4.5	19.25	1626T-47-33	1997		3.375	4.5	19.25	1635T-47-33	2726
5.875	2.875	4.5	19.25	1620T-57-27	1536	5.875	2.875	4.5	19.75	1626T-57-27	2055	5.875	2.875	4.5	19.75	1635T-57-27	2806
	3.875	4.5	20.25	1620T-57-37	1626		3.875	4.5	20.75	1626T-57-37	2172		3.875	4.5	20.75	1635T-57-37	2966
	4.875	4.5	21.25	1620T-57-47	1716		4.875	4.5	21.75	1626T-57-47	2289		4.875	4.5	21.75	1635T-57-47	3125

WHEN ORDERING, PLEASE SPECIFY:

- 1. Quantity & Item Number
- 2. No. 1, No. 2, No. 3, or No. 7 Steel
- 3. Locating Ring Item Number
- 4. E, O and R Dimensions
- 5. L Dimension (Leader Pin Length)
- 6. Method of Shipment

For detailed dimensions, see corresponding size "A" Series Mold Bases.

NOTE: For 3-Plate Extension Bushings, see page 195.